


# Nanoclass Square Pro Membrane KE

## Product Range



## Features



## Applications



## Filter Class



## KEY FACTS

- High efficiency (H14 > 99.995 % at MPPS)
- Integral knife-edge for use with gel-seal grid ceiling systems
- Available in depth of 109 mm
- High tensile strength
- 100% boron free
- Minipleat technology for laminar flow
- Extremely low pressure drop
- Guaranteed leak free

## DESIGN

e-PTFE membrane filter media folded into a pack and sealed into an anodized aluminum frame with integrated knife-edge.

## APPLICATIONS

Final filter for clean rooms and clean workbenches that use gel-seal grid systems. For separation of viruses, bacteria, toxic dust and aerosols, in hospitals/medical institutes, chemists, laboratories, clean rooms, pharmacy, food processing industry, microelectronics.

# Nanoclass Square Pro Membrane KE

## PERFORMANCE DATA

Filter Class	Dimensions	Flow Rate	Pressure Drop	Filter Class	Dimensions	Flow Rate	Pressure Drop
EN 1822	mm	m <sup>3</sup> /h	Pa	EN 1822	mm	m <sup>3</sup> /h	Pa
H14	305 x 305 x 109	150	55	H14	610 x 762 x 109	750	55
H14	305 x 610 x 109	300	55	H14	610 x 915 x 109	900	55
H14	305 x 762 x 109	375	55	H14	610 x 1220 x 109	1200	55
H14	305 x 915 x 109	450	55	H14	762 x 915 x 109	1130	55
H14	457 x 457 x 109	350	55	H14	762 x 1220 x 109	1500	55
H14	457 x 610 x 109	450	55	H14	1220 x 1220 x 109	2400	55
H14	610 x 610 x 109	600	55	H14	1220 x 1220 x 109	2400	55

## SPECIFICATION

<b>Recommended air flow</b>	Flow rate $\pm$ 10 %	<b>Recommended final pressure drop</b>	450 Pa (max. 600 Pa)
<b>Heat resistance</b>	Up to 70 °C (Peak 90 °C)	<b>Moisture resistance</b>	100 % rel. humidity
<b>Regenerable</b>	No	<b>Incinerable</b>	No

## OPTIONS

<b>Gasket</b>	Continuous polyurethane foam or flat neoprene
<b>Grid</b>	1 or 2 sides